

Réglages du coupleur MFJ-945E avec antenne FD4 home made

Bande	F (MHz)	Inductance	Transmitter	Antenna	SWR
80	3,500	D	6,00	3,50	1,10
	3,530	D	6,00	3,50	1,10
	3,560	D	6,00	3,90	1,10
	3,600	D	6,50	4,10	1,30
	3,650	D	6,60	4,30	1,50
	3,700	D	6,20	5,00	1,20
	3,750	D	6,20	5,50	1,30
	3,800	D	6,00	5,50	1,20
	40	7,000	H	2,90	4,90
7,020		H	2,90	4,90	1,10
7,040		H	3,00	4,60	1,10
7,060		H	3,00	4,60	1,10
7,100		H	3,00	4,60	1,10
7,150		H	3,00	4,60	1,05
7,200		H	3,00	4,60	1,05
30		10,100	J	3,30	3,60
	10,120	J	3,30	3,80	1,10
	10,150	J	3,30	4,20	1,10
20	14,000	K	4,10	3,20	1,00
	14,030	K	4,10	3,20	1,00
	14,060	K	4,10	3,20	1,00
	14,100	K	3,90	4,00	1,00
	14,200	K	3,90	4,10	1,00
	14,300	K	3,90	4,50	1,00
	14,350	K	3,90	4,60	1,00
10	28,000	B	6,00	2,00	1,10
	28,050	B	6,00	2,00	1,10
	28,100	B	6,00	2,00	1,10
	28,150	B	6,00	2,00	1,10
	28,200	B	6,00	3,00	1,10
	28,500	A	5,20	6,80	1,15
	29,000	J	6,20	6,50	1,20
	29,350	K	7,00	4,00	1,15
	29,700	K	7,00	4,00	1,15